

SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

CONTROLLER AND METHOD FOR CONTROLLING REGENERATION OF A WATER SOFTENER

Background of Invention

[0001] The present invention is generally related to water softeners, and, more particularly, to a controller and method for controlling regeneration of a water softener based on the total hardness (e.g., concentration of calcium carbonate) removed from the influent water to the softener. Here, total hardness is defined as the hardness of the water times the total volume of water softened.

[0002] Municipal water treatment plants often draw water from several sources that vary in hardness. For example, when the source of the water is groundwater, the water can be relatively hard, which is equivalent to, for example, a high concentration of calcium carbonate. However, when the source of the water is surface water, the water can be relatively soft, such as characterized by a low concentration of calcium carbonate. Many municipal water treatment plants use both types of water in varying proportions. The proportion of hard and soft water used by a municipal water treatment plant may also vary over time. Therefore, the hardness of the water actually delivered to the consumer can vary considerably throughout the year. Many consumers use water softeners to soften the water used in their homes, the work place, schools, etc. These water softeners are typically preset to soften water of a predefined degree of hardness. The presetting action assumes that the predefined hardness of the influent water to the softener remains constant.

[0003] Thus, in the past, it has been assumed that the hardness of the influent water to

the water softener remained constant. Further, it is believed that the only variable that water softeners have been known to measure is the volume of water treated by the softener. Hence, if the water hardness varied, the softener would undesirably regenerate prematurely or not often enough.

[0004] In view of the foregoing considerations it would be desirable to provide a water softener and techniques that permit measuring the variability of the hardness of the water over time. It would be further desirable to provide a water softener with a regeneration controller programmed to regenerate the softener based on the total hardness removed from the influent water, as opposed to based on an assumption likely to incorrectly reflect the actual composition of the water. It would be further desirable to provide a regeneration technique that avoids any unnecessary discharge of salt (e.g., brine) to the surrounding environment.

Summary of Invention

[0005] Generally, the present invention fulfills the foregoing needs by providing in one aspect thereof, a regeneration controller for a water softener comprising a water meter configured to output a signal indicative of the volume of influent water received by the water softener. A water-hardness indicator, such as a conductivity meter or an ion-selective electrode, is configured to output a signal indicative of a degree of water hardness of the influent water, such as may be indicated by a conductivity measurement or a calcium concentration measurement, respectively. A processor is coupled to receive the respective signals from the water meter and the water-hardness indicator. The processor is further configured to calculate a value indicative of the total level of hardness removed by the water softener. A comparator is coupled to receive a signal indicative of the quantity of resin capacity of the water softener. The comparator is further configured to receive the value indicative of total hardness to issue a regeneration command based on comparing the resin capacity relative to the value of total hardness.

[0006] In another aspect thereof, the present invention further fulfills the foregoing needs by providing a method for controlling regeneration of a water softener. The method allows measuring the volume of influent water received by the water softener. The method further allows measuring a signal indicative of a degree of hardness of

the influent water, such as by measuring the degree of conductivity of the influent water or the concentration of calcium in the water. A value indicative of the total quantity of hardness removed by the water softener is calculated. The resin capacity of the water softener is provided, e.g., is known. The resin capacity is related to the value of total hardness to determine whether or not regeneration is to be commanded for the water softener.

Brief Description of Drawings

[0007] The features and advantages of the present invention will become apparent from the following detailed description of the invention when read with the accompanying drawing in which:

[0008] FIG. 1 is a block diagram of an exemplary regeneration controller that, in accordance with aspects of the present invention, may be configured to issue a command to regenerate the softener based on the total hardness actually removed from the influent water.

Detailed Description

[0009] Below is generic background information solely for the purpose of providing a cursory description of one exemplary operation of a typical water softener. This background information in no way should be construed as limiting the scope of the present invention described further below. A water conditioner may comprise at least two tanks: a resin tank and a brine (e.g., salt) tank. The resin tank is filled with a resin that, for example, comprises relatively small beads of cross-linked polystyrene sulfonic acid. This resin may be referred to in the art as a cation resin. The beads may be constructed to exhibit a permanent electrical charge. The charge may cause the beads to attract positively charged ions. For example, the resin may be initially placed into service with Na^+ ions on the beads. When the hardness ions (e.g., Ca^{2+} and Mg^{2+}) come in contact with the Na^+ , such ions would displace the Na^+ on the beads. The Na^+ is eventually dissolved into the water. This sodium generally leaves the resin tank and may be delivered to the tap with the treated water. In theory, when most of the Na^+ is removed from the resin beads, regeneration equipment should start the regeneration process. As explained in the background section of the present specification, prior to the present invention, in practice, the regeneration process

[0011] FIG. 1 is a block diagram of an exemplary regeneration controller 10 configured to issue a command to regenerate the softener based on the total hardness removed from the influent water. As shown in FIG. 1, controller 10 includes a water meter 12 for supplying a signal indicative of the volume of influent water to the water softener. Controller 10 further includes a water-hardness indicator 14 configured to output a signal indicative of a degree of the water hardness of the influent water. In one exemplary embodiment, the water-hardness indicator comprises a conductivity meter configured to measure the conductivity (e.g., microsiemens) of the influent water. In another exemplary embodiment, the water-hardness indicator comprises an ion-selective electrode configured, for example, to measure the concentration (e.g., mg/L) of calcium of the influent water to the softener. Although FIG. 1 illustrates water meter 12 to be upstream relative to water-hardness indicator 14, it will be appreciated that

the specific placement of the water meter relative to the water-hardness indicator is of no consequence for purposes of the present invention, and, accordingly, the specific block placement shown in FIG. 1 should not be construed as limiting the invention. Examples of conductivity meters that may be used include conductivity meter, Model No. Sension 5, available from Hach Company, Model No. 3100, available from YSI Incorporated, Model No. 130A, available from Thermo Orion. Examples of ion-selective electrodes that may be used for measuring calcium concentration include Model Nos. A27504-06 and A-27504-34 available from Cole-Parmer.

[0012] Since the conductivity of the influent water is a function of the total dissolved solids in the water, the conductivity of the water comprises an indication or suggests an approximate measure of the hardness of the water. Accordingly, in one exemplary embodiment a processor 16 may include a memory 18 for storing a functional relationship or a look-up table for relating the degree of conductivity of the influent water as may be measured by a conductivity meter to a degree of hardness (grains/gallon) of the influent water to the softener. In another exemplary embodiment, memory 18 may be configured for storing a functional relationship or a look-up table for relating the degree of calcium ion concentration, as may be measured by an ion-selective electrode to a degree of hardness of the influent water. In each case, such a relationship or look-up table may be experimentally and/or analytically derived using techniques well understood by those skilled in the art.

[0013] For readers desirous of general background information regarding the physical basis for relating the water conductivity and water hardness, reference is made to textbook titled "Standard Methods for the Examination of Water and Wastewater," edited by L.S. Clesceri, A.E. Greenberg & R.R. Rhodes Truessell, 17th Edition, 1989, and, more specifically, see table 2510:1, page 2-60 for an illustration for relating concentration of potassium chloride to conductivity measurements.

[0014] In one exemplary embodiment, the degree of hardness can be calculated as follows: Divide concentration (molarity) of potassium chloride by 2 = concentration of calcium (molarity). Multiply the concentration of calcium (molarity) by 40 gm/mole = concentration of calcium (gm/L). Multiply the concentration of calcium (gm/L) by 2.5 = concentration of hardness (gm/L) or CaCO_3 . Grains of hardness (grains/gal) =

skill in the art without departing from the invention herein. Accordingly, it is intended that the invention be limited only by the spirit and scope of the appended claims.